# NATIONAL AIR INTELLIGENCE CENTER



SCINTILLATION AND DANCING OF LASER BEAM PROPAGATION IN MARINE ATMOSPHERE

by

Yang Gaochao, Han Shouchung, et al.





Approved for public release: distribution unlimited

19960618 138

## **HUMAN TRANSLATION**

NAIC-ID(RS)T-0143-96

17 April 1996

MICROFICHE NR: 96000327

SCINTILLATION AND DANCING OF LASER BEAM PROPAGATION IN MARINE ATMOSPHERE

By: Yang Gaochao, Han Shouchung, et al.

English pages: 9

Source: Jiguang Jishu (Laser Technology), Vol. 15, Nr. 2,

April 1991; pp. 104-107

Country of origin: China

Translated by: Leo Kanner Associates

F33657-88-D-2188

Requester: NAIC/TATD/Bruce Armstrong

Approved for public release: distribution unlimited.

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE NATIONAL AIR INTELLIGENCE CENTER.

PREPARED BY:

TRANSLATION SERVICES
NATIONAL AIR INTELLIGENCE CENTER
WPAFB, OHIO

### GRAPHICS DISCLAIMER

All figures, graphics, tables, equations, etc. merged into this translation were extracted from the best quality copy available.

SCINTILLATION AND DANCING OF LASER BEAM PROPAGATION IN MARINE ATMOSPHERE

Yang Gaochao, Han Shouchung, Liu Xiaochung, Shao Shisheng, Hu Ming, Rao Ruizhong, and Song Zhengfang

Anhui Institute of Optics and Fine Mechanics, Chinese Academy of Sciences, Hefei

Abstract: In this paper, experimental results of intensity fluctuation (scintillation) and dancing (angle-of-arrival fluctuation and isoplanatic angle) of laser beam at Dawanshan Islands are reported. The results are comparied with the data of turbulent intensity measured simulteneously. It is indicated that the turbulence in marine atmosphere of the South China Sea during late autumn and early winter is rather violent, and it's effect on laser propagation is remarkable.

#### I. Introduction

As early as the early sixties, the possibilities of marine applications of lasers began to be studied. By now, multiple laser engineering projects on airborne marine bathymeters and pollution measurement with lasers have been developed. Since the laser beam in these engineering projects has to penetrate the atmosphere at the sea surface, and is affected by atmospheric

turbulence, properties of laser intensity fluctuations
(scintillation) and dancing (fluctuations in angle of arrival and
fluctuations in isoplanatic angle) have practical significance on
the design and applications of marine laser projects.

From late October to mid-November 1989, the authors conducted measurements on laser scintillation and dancing at Dawanshan Islands in the South China Sea. Moreover, turbulence intensities were observed in order to understand the atmospheric properties. The article reports the observation results on scintillation and dancing with an analysis based on present-day theory.

# II. General Situation of Measurements

The experiments were conducted at Dawanshan Island and Xiaowanshan Island in the South China Sea. Two transmission light paths were selected, with distances of 1800m and 500m, respectively. Our base was established at the west end of Wanshan Village on Dawanshan Island. When carrying out long-distance experiments, a reflective mirror set up on a rock in the southeast part of Xiaowashan Island reflected the laser beams. While conducting short-distance experiments, the laser device (direct optical path) or the reflective mirror (reflective light path) were set up on a rock across the bay from the other site. The light path was about 12m above the sea surface.

In the scintillation and dancing experiments, an He-Ne laser ( $\lambda$ =0.6328 $\mu$ m) was used. Fig. 1 shows the experimental setup.




Fig. 1. Brief experimental setup

LEGEND: 1 - He-Ne laser 2 - atmosphere 3 - receiving

telescope 4 - detector 5 - amplification 6 - data collector

7 - computer

Without passing through a telescope, the laser beam directly illuminated (or reflected, after passing a flat reflective mirror) onto a refractive or an OD200mm receiving telescope; electrical signals were converted with a detector. After amplification, the signal was fed to a microcomputer for processing via a data collector. During scintillation measurements, an optoelectronic multiplier was used in the detector. During the dancing measurements, a four-quadrant silicon optoelectronic diode was used. The nonlinear problems of the detector were corrected with a computer. The minimum angle of resolution of the system was 0.78µradian; the overall measurement error was approximately 5%. The measurement error is directly related to the nonlinearity and reception of the detector, mechanical stabilization of the emitting system, and the performance of the multichannel data amplifier.

#### III. Experimental Results

#### 1. Scintillation

From November 7 to 9, scintillation of the He-Ne laser between Dawanshan and Xiaowanshan islands was measured with the reflecting optical path. Overall, 160 data sets were measured.

The data processing method is the same as in [1]. Fig. 2 gives the time-dependent variation of the logarithmic intensity variance  $\sigma_{\rm lnI}2$  on November 8, from 1100 hours to 2300 hours. The situations indicated in the figure are very typical. On the morning of that day, there were thin clouds at high altitudes. At about 1230 hours, the weather turned cloudy. After 1600 hours, the weather turned sunny, until sunset. The scintillation intensity apparently varied with the weather conditions. At night,  $\sigma_{\rm lnI}2$  gradually weakened, but was still greater than on cloudy days. This variation is mainly due to insolation that we had measured several times previously. Undoubtedly, this matches the general rule.




Fig. 2. Diurnal variation of scintillation (at Dawanshan on November 8, 1989)

Theoretically, the scintillation intensity (spherical surface wave) of the reflective optical path is [2]

$$\sigma_{1al}^{2} = 2 \times 0.496C_{\bullet}^{2} k^{7/6} (2L)^{11/6}$$
 (1)

In the equation,  $C_n 2$  is the turbulence intensity,  $k=2\pi/\lambda$ .  $\lambda$  is the wavelength of the laser; L is the transmission distance. On

the right-hand side of the equation, the factor 2 is the number of applications of the reflective optical path. Now  $\lambda=0.6328\lambda$  and L=1.8km. Thus, we can calculate that the mean turbulence intensity on the optical path is

$$C_{\pi^2} = 2.092 \times 10^{-15} \sigma_{\text{tal}^2}$$
 (2)

The foregoing equation applies to the case of a pointwise receiving aperture. In actual application, an OD200mm receiving aperture was used. Hence, the aperture-smoothing factor is required for revision. From the theoretical curve, we obtain  $\theta$  approximately equal to 0.02. Therefore,

$$C_{n}^{2} = 1.05 \times 10^{-13} \sigma_{1n}^{2} \tag{3}$$

The measured  $\sigma_{\rm in1}2$  is 0.7 at the maximum, and 0.02 at the minimum. Thus, we know that the variation range of  $C_{\rm n}2$  is between 2x10-15 and 7x10-14m<sup>-2/3</sup>. The result is quite consistent with the result of temperature fluctuation measurements (in the latter case, the maximum is  $9x10-14m^{-2/3}$ , and the minimum is  $1.7x10-15m^{-2/3}$ ). As for comparison point-by-point, since the turbulence detector was set up at a site that was not in the light path, during the measurements, synchronization was not carried out, therefore, it was unable to be proceeded with. However, as the average, the daylight average for scintillation intensity is 0.27 (1100 to 1500 hours at November 9). The converted  $C_{\rm n}2$  is  $2.7x10-14m^{-2/3}$ , which is smaller than the mean daylight result for temperature fluctuation measurements at  $5x10-14m^{-2/3}$ . This can be understood because the light path was

almost entirely over the empty sea surface, but the turbulence detector was set up on a slope greatly affected by terrain, so that more intensive turbulence was measured.

#### 2. Dancing

Light-beam dancing was measured by using a four-quadrant optoelectronic diode system, which is detailed in reference [3]. At Wanshan, the authors measured the dancing of direct light path by using 5m as the optical path, acquiring a total of 38 data sets (refer to Table 1). In the system, we also can measure the fluctuations in light intensity, to derive the isoplanatic angle with a theoretical formula. The theoretical relationships of fluctuations in the angle of arrival and in the isoplanatic angle are, respectively:

$$\sigma_{\pi}^{2} = 2.912C_{\pi}^{2} LD^{-1/3} \tag{4}$$

$$\theta_{*} = 0.9676 \left( \log(1 + \sigma_{*}^{2} / S^{2}) \right)$$
 (5)

In the equations, D is the aperture of the receiving telescope;  $\sigma_a 2$  is the variation of signal fluctuation; S is the average value of the signal. Thus, we know that the average refractivity structure constants  $C_n 2(\alpha)$  and  $C_n 2(\theta_0)$  are:

$$C_{\pi^{-}}(\alpha) = 1.07 \times 10^{-3} \sigma_{\alpha}^{-2}$$

$$C_{\pi^{-}}(\theta_{0}) = 1.48 \times 10^{-22} \theta_{0}^{-2}$$
(6)

With respect to Eq. (7), the aperture-smoothing factor  $(\theta_0=0.1)$  was calculated.

TABLE 1. Measurement Values of Standard Difference of Angle of Arrival and Isoplanatic Angle

a E	期 b	时间	σα	$C_{\pm}^{2}(\alpha)$	$\theta_{\mathrm{c}}$	$C_z^2(\theta_c)$
11/0	89	20:08	7.54E-06	6.100177E-14	9.11E-06	3.71692E-14
11/0	9 / 89	20:28	3.09E-06	1.024511E-14	0.0000184	1.151729E-14
11/0	9 / 89	20:38	3.54E-06	1.344641E-14	0.0000139	1.838044E-14
11/0		20:48	3.32E-06	1.182704E-14	0.0000141	1.794794E-14
11/0		21:05	2.91E-06	9.086271E-15	0.0000159	1.469099E-14
11/0		21:17	3.31E-06	1.17559E-14	0.0000253	6.774007E-15
11/0		21:28	4.73E-06	2.400612E-14	7.74E-06	4.876913E-14
11/0		21:39	2.72E-06	7.938483E-15	0.0000277	5.824342E-15
11/1	0 / 89	09:45	0.000003	9.657001E-15	0.0000455	2.546992E-15
11/1		09:58	4.69E-06	2.360182E-14	0.000018	1.1947E-14
11/1		10:10	4.52E-06	2.192182E-14	0.0000134	1.953767E-14
11/1		10:28	3.89E-06	1.623674E-14	0.000018	1.1947E-14
11/1		10:38	5.24E-06	2.946201E-14	0.0000232	7.826484E-15
11/1		10:48	4.21E-06	1.901796E-14	0.0000235	7.660672E-15
11/1		11:11	3.95E-06	1.674148E-14	0.0000261	6.43151E-15
11/1		11:36	3.46E-06	1.284553E-14	0.0000196	1.036621E-14
11/1		11:48	5.08E-06	2.769027E-14	0.0000185	1.141372E-14
11/1		11:58	3.88E-06	1.615337E-14	0.0000151	1.601098E-14
11/1		12:15	4.32E-06	2.002475E-14	0.0000137	1.882979E-14
11/1		12:25	8.35E-06	7.481224E-14	5.65E-06	8.240728E-14
11/1		12:38	4.38E-06	2.058486E-14	0.0000176	1.240297E-14
11/1		12:50	3.83E-06	1.573973E-14	0.0000159	1.469099E-14
11/1		13:02	3.83E-06	1.573973E-14	0.000037	3.595097E-15
11/1		14:41	3.15E-06	1.064684E-1;	0.0000439	2.703581E-15
11/1		14:51	0.0000034	1.240388E-14	0.0000353	3.888266E-15
11/(1		15 : 02	2.43E-06	6.335958E-15	0.0000484	2.297762E-15
11/1		15:13	0.0000024	6.18048E-15	0.000044	2.693349E-15
11 (1		15 : 25	5.73E-06	3.52297 E-14	0.0000135	1.929703E-14
11/1		15 : 35	3.15E-06	1.064684E-14	0.0000269	6.115888E-15
11/1		15:46	3.37E-06	1.218596E-14	0.0000251	6.864213E-15
$11 \times 1$		16:02	4.78E-06	2.451633E-14	0.0000173	1.276348E-14
11/1		16 : 28	2.28E-06	5.577883E-15	0.0000381	3.423781E-15
11/1		16:45	0.0000064	4.395008E-14	0.0000118	2.414963E-14
11,/1		16:51	0.0000067	4.816697E-11	7.27E-06	5.413634E-14
11/1		17:08	4.62E-06	2.290254E-14	0.000016	1.453829E-14
11/1		17:19	2.46E-06	6.493367E-15	0.0000371	3.57896E-15
11/1		17 : 28	6.47E-06	4.491675E-11	5.94E-06	7.581168E-14
11/1	0 / 89	17:42	3.56E-06	1.359877E-14	9.78E-06	3.30229E-14

KEY: a - date b - time

From Table 1, the maximum dancing angle of the mean square root of the light beam is  $8.4\mu radians$ ; the minimum measured was  $2.3\mu radians$ . The corresponding value of  $C_n 2$  (a) is between  $5.6 \times 10$ -15 and  $7.5 \times 10$ -14m<sup>-2/3</sup>. As for scintillation, its value

can be compared with the measurement results of temperature fluctuations. As for the reason why no smaller value than  $2\mu radians$  were obtained, it is possibly related to system error. The isoplanatic angle  $\theta_0$  varies between 5.7 and  $18\mu radians$ . The variation range for the converted  $C_n 2(\theta)$  is between  $2.3 \times 10^{-15}$  and  $8.2 \times 10^{-14} m^{-2/3}$ . These values are relatively closer to the measured results of temperature fluctuations.

 $\sigma_a$  and  $\theta_0$  were obtained from measurement with the same sign. The average equivalent turbulence intensity was quite consistent, at 2.09 x10-14m and 1.75x10-14m^2/3. However, the correlation coefficient of the two is about 0.8. Theoretically, the fluctuation of the oscillation amplitude should be related to the phase fluctuation. The fact of not entirely correlating is possibly traceable to some problems in measurements. As indicted from some theoretical analysis, the measurement of the isoplanatic angle should apply an OD110mm receiver aperture about but we used the OD200mm receiving telescope. Besides if there are other regions, such as theoretical problems, this point will be in our latter work.

#### IV. Preliminary Conclusions

As indicated by the measurement results of scintillation, the atmospheric turbulence was still quite high in the sea territory of Dawanshan Islands in the late fall and early winter. If based on the relationship  $Z^{-4/3}$  between turbulence intensity and altitude to be derived to a height of 1.5m above the sea

surface, then the turbulence intensity is approximately between 3x10-14 and  $1x10-12m^{-2/3}$ . These values are fundamentally in the range between intermediate to high turbulence in the atmosphere on the ground surface. The reason is apparently related to local climate. Since its latitude is relatively low (21°56′min N. Lat.), insolation is still intensive even in the late fall and the early winter. The average temperature may be between 22 and  $27^{\circ}$ C. The temperature at night was still not low; temperatures at 2100 hours corresponded to the temperature at 0900 hours. Our measurement results clearly indicate this property. Therefore, the above-mentioned features should be noted when designing and applying laser engineering projects for marine investigations.

The authors are grateful to vigorous support by the Dawanshan Marine Station, the South China Sea Branch of the State Marine Administration.

# DISTRIBUTION LIST

# DISTRIBUTION DIRECT TO RECIPIENT

ORGANIZATION	MICROFICHE
BO85 DIA/RTS-2FI	1
C509 BALLOC509 BALLISTIC RES LAB	1
C510 R&T LABS/AVEADCOM	1
C513 ARRADCOM	1
C535 AVRADCOM/TSARCOM	1
C539 TRASANA	1
Q592 FSTC	4
Q619 MSIC REDSTONE	1
Q008 NTIC	1
Q043 AFMIC-IS	1
E404 AEDC/DOF	1
E410 AFDTC/IN	1
E429 SD/IND	1
P005 DOE/ISA/DDI	1
1051 AFIT/LDE	1
PO90 NSA/CDB	1

Microfiche Nbr: FTD96C000327

NAIC-ID(RS)T-0143-96